BAROID PARLLIBURTON

CON DET®

Wetting Agent

Description

CON DET® proprietary blend of anionic surfactants is specially formulated for use in fresh water, salt water, and in low-solids drilling fluids as a wetting agent.

Applications/Functions

- Can keep the drill bit clean
- Can slow breakup of cuttings in the annulus while being pumped to the surface
- Can counteract the sticking tendencies of clays, thereby reducing wall packing, bit balling, booting-off, and formation of mud rings
- Can promote settling of cuttings at the surface in low solids fluid systems

Advantages

- Effective in low concentrations
- · Easy to mix with water
- Biodegradable
- Compatible with other Baroid products

Typical Properties

•	Appearance	Clear red liquid
•	Specific gravity	1.03
•	pH (1 % solution)	8.9
•	Flash point, PMCC °F, °C	210 (99)
•	Pour point, °F, °C	28 (-2.2)

Recommended Treatment

Approximate Amounts of CON DET Wetting Agent Added to Fresh or Salt Water			
Desired Condition/Result	Amount/ 100 gal	Amount/ bbl	Liters/m ³
To promote bit cleaning and to settle cuttings	2 – 4 pints	1 – 2 pints	2 – 5 liters
To reduce stickiness of clays	1 – 6 quarts	1 – 3 quarts	5 – 12 liters

Packaging

CON DET wetting agent is packaged in 5-gal (19-liters) plastic containers.

Availability

CON DET wetting agent can be purchased through any Baroid Industrial Drilling Products Retailer. To locate the Baroid IDP retailer nearest you contact the Customer Service Department in Houston or your area IDP Sales Representative.

Baroid Industrial Drilling Products

Product Service Line, Halliburton

3000 N. Sam Houston Pkwy E.

Houston, TX 77032

 Customer Service
 (800) 735-6075 Toll Free
 (281) 871-4612

 Technical Service
 (877) 379-7412 Toll Free
 (281) 871-4613